

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

IN THE CLAIMS

Please cancel claims 7, 34, 55, 75, 91, 107, 122 and 133.

Please add claim 146.

Please amend claims 1, 4, 8, 26, 31, 44, 53, 65, 72, 84, 88, 100, 104, 116, 119, 130 and 132 as follows:

1.(Currently Amended) A surgical cutting instrument for use with a motor having a drive mechanism, the instrument comprising:

| an outer tube defining a first curved segment, a proximal region terminating at a proximal end, a distal region terminating at a distal end, and a lumen extending from the proximal end to the distal end, the lumen being defined by an inner surface of the outer tube;

| an inner wire assembly received within the lumen and comprising a wire, the inner wire assembly including a proximal section and a distal section, wherein the proximal section extends proximally from the proximal end of the outer tube;

| a cutting tip connected to the distal section of the inner wire assembly, wherein at least a portion of the cutting tip extends distal the distal end of the outer tube;

| a coupling chuck secured to the proximal section of the inner wire assembly, wherein the coupling chuck is adapted for connection to a drive mechanism of a motor; and

| a housing maintaining the proximal region of the outer tube and the coupling chuck, the housing being adapted for connection to a motor;

| wherein a rotating journal bearing is established between an outer surface of the inner wire assembly and an entirety of a length of the inner surface of the outer tube distal the housing upon rotation of the inner wire assembly relative to the outer tube;

| wherein upon final assembly, the wire assumes a shape of the first curved segment;

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

and further wherein the instrument is configured to allow rotation of the inner wire assembly relative to the outer tube at a speed in excess of 50,000 RPM without failure of the bearing.

2.(Original) The instrument of claim 1, wherein the instrument is characterized by the absence of a ball bearing assembly between the outer tube and the inner wire assembly.

3.(Original) The instrument of claim 1, further comprising:
a lubricant disposed between the outer surface of the inner wire assembly and the inner surface of the outer tube;
wherein upon rotation of the inner wire assembly relative to the outer tube, the lubricant is adapted to create a hydrodynamic effect between the inner wire assembly and the outer tube.

4.(Currently Amended) The instrument of claim 1, wherein the ~~inner-wire assembly is a homogenous-wire.~~

5.(Original) The instrument of claim 4, wherein the wire is a tool steel.

6.(Cancelled)

7.(Cancelled)

8.(Currently Amended) The instrument of claim ~~7~~1, wherein the outer tube further defines a second curved segment apart from the first curved section, and further wherein upon final assembly, the wire assumes a shape of the second curved segment.

9.(Original) The instrument of claim 4, wherein at least a portion of the outer tube distal the housing has a maximum outer diameter of not more than 2 mm.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

10.(Original) The instrument of claim 4, wherein the wire has an outer diameter of not more than 0.8 mm.

11.(Original) The instrument of claim 4, wherein an exposed portion of the wire extends distally from the distal end of the outer tube, and further wherein a length of the exposed portion is not greater than 2.54 mm.

12.(Original) The instrument of claim 4, wherein the distal region of the outer tube tapers distally in diameter to the distal end.

13.(Withdrawn) The instrument of claim 1, further comprising:

a sealing tip connected to the distal region of the outer tube, at least a portion of the sealing tip defining an inner diameter that is less than a diameter of the lumen of the outer tube.

14.(Withdrawn) The instrument of claim 13, wherein the sealing tip is a ceramic body.

15.(Withdrawn) The instrument of claim 13, wherein the sealing tip is a tubular body having a proximal portion and a distal portion, the distal portion defining a relaxed state diameter that is less than a diameter of the inner wire assembly, and further wherein upon final assembly, the distal portion of the sealing tip is forced to an expanded state diameter via contact with the inner wire assembly.

16.(Withdrawn) The instrument of claim 13, wherein the sealing tip is a tubular body shrunk fit to the outer tube and a portion of the inner wire assembly.

17.(Withdrawn) The instrument of claim 1, further comprising:

a cooling sleeve disposed over at least a portion of the outer tube.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

18.(Withdrawn) The instrument of claim 1, wherein the inner wire assembly further defines an intermediate section comprised of a flexible, multi-stranded coil of wires, the intermediate section being connected at opposite ends thereof to the proximal and distal sections, respectively.

19.(Withdrawn) The instrument of claim 18, wherein the proximal and distal sections are wires.

20.(Withdrawn) The instrument of claim 18, wherein at least a portion of the rotating journal bearing is established between the inner surface of the outer tube and the flexible wound coil of wires.

21.(Withdrawn) The instrument of claim 18, wherein the outer tube defines a curved segment, and further wherein upon final assembly, the flexible coil of wires assumes a shape of the curved segment.

22.(Withdrawn) The instrument of claim 1, wherein the inner wire assembly includes a first portion and a second portion, the first portion being a rigid wire and the second portion being a flexible wire, and further wherein the second portion is connected to, and extends distally from, a distal end of the first portion, the cutting tip being connected distal a distal end of the second portion.

23.(Withdrawn) The instrument of claim 22, wherein the outer tube defines a curved segment, and further wherein upon final assembly, the second portion of the inner wire assembly assumes a shape of the curved segment.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

24.(Withdrawn) The instrument of claim 23, further comprising:
an intermediate tube disposed between the inner surface of the outer tube and an outer surface of the second portion of the inner wire assembly along the curved segment of the outer tube.

25.(Withdrawn) The instrument of claim 22, wherein the second portion has a diameter less than a diameter of the first portion.

26.(Currently Amended) A surgical cutting instrument for use with a motor having a drive mechanism, the instrument comprising:

| an outer tube defining a first curved segment, a proximal region terminating at a proximal end, a distal region terminating at a distal end, and a lumen extending from the proximal end to the distal end, the lumen being defined by an inner surface of the outer tube;

| an inner wire assembly received within the lumen and comprising a wire, the inner wire assembly including a proximal section and a distal section, wherein the proximal section extends proximally from the proximal end of the outer tube;

| a grease lubricant disposed between the inner surface of the outer tube and an outer surface of the inner wire assembly, the grease lubricant exhibiting a dynamic viscosity of not less than 100 mm²/s at 40° C;

| a cutting tip connected to the distal section of the inner wire assembly, wherein at least a portion of the cutting tip extends distal the distal end of the outer tube;

| a coupling chuck secured to the proximal section of the inner wire assembly, wherein the coupling chuck is adapted for connection to a drive mechanism of a motor; and

| a housing maintaining the proximal region of the outer tube and the coupling chuck, the housing being adapted for connection to a motor;

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

wherein a hydrodynamic, rotating journal bearing is established by the grease lubricant between an outer surface of at least a portion of the inner wire assembly and the inner surface of the outer tube distal the housing upon rotation of the inner wire assembly relative to the outer tube;

wherein upon final assembly, the wire assumes a shape of the first curved segment;

and further wherein the instrument is configured to allow rotation of the inner wire assembly relative to the outer tube at a speed in excess of 50,000 RPM, without failure of the bearing.

27.(Original) The instrument of claim 26, wherein the grease lubricant exhibits a dynamic viscosity in the range of 150 – 250 mm²/s at 40°C.

28.(Original) The instrument of claim 26, wherein the grease lubricant is a synthetic hydrocarbon thickened with silica.

29.(Original) The instrument of claim 26, wherein the grease lubricant is hydrophobic.

30.(Original) The instrument of claim 26, wherein the instrument is characterized by the absence of a ball bearing assembly between the outer tube and the inner wire assembly.

31.(Currently Amended) The instrument of claim 26, wherein the ~~inner-wire assembly~~ is a homogenous-wire.

32.(Original) The instrument of claim 31, wherein the wire is a tool steel.

33.(Original) The instrument of claim 31, wherein the hydrodynamic bearing is established along an entirety of a length of the outer tube distal the housing.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

34.(Cancelled)

35.(Original) The instrument of claim 31, wherein at least a portion of the outer tube distal the housing has a maximum outer diameter of not more than 2 mm.

36.(Original) The instrument of claim 31, wherein the wire has an outer diameter of not more than 0.8 mm.

37.(Original) The instrument of claim 31, wherein an exposed portion of the wire extends distally from the distal end of the outer tube, and further wherein a length of the exposed portion is not greater than 2.54 mm.

38.(Original) The instrument of claim 31, wherein the distal region of the outer tube tapers distally in diameter to the distal end.

39.(Withdrawn) The instrument of claim 26, further comprising:

a sealing tip connected to the distal region of the outer tube, at least a portion of the sealing tip defining an inner diameter that is less than a diameter of the lumen of the outer tube.

40.(Withdrawn) The instrument of claim 39, wherein the sealing tip is a ceramic body.

41.(Withdrawn) The instrument of claim 39, wherein the sealing tip is a tubular body having a proximal portion and a distal portion, the distal portion defining a relaxed state diameter that is less than a diameter of the inner wire assembly, and further wherein upon final assembly, the distal portion of the sealing tip is forced to an expanded state diameter via contact with the inner wire assembly.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

42.(Withdrawn) The instrument of claim 39, wherein the sealing tip is a tubular body shrunk fit to the outer tube and a portion of the inner wire assembly.

43.(Withdrawn) The instrument of claim 26, further comprising:
a cooling sleeve disposed over at least a portion of the outer tube.

44.(Currently Amended) A surgical cutting instrument for use with a motor having a drive mechanism, the instrument comprising:

an outer tube defining a first curved segment, a proximal region terminating at a proximal end, a distal region terminating at a distal end, and a lumen extending from the proximal end to the distal end, the lumen being defined by an inner surface of the outer tube;

an inner wire assembly received within the lumen and comprising a wire, the inner wire assembly including a proximal section and a distal section, wherein the proximal section extends proximally from the proximal end of the outer tube, and further wherein the inner wire assembly is formed of a material exhibiting a fatigue strength of at least 75 Kpsi;

a cutting tip connected to the distal section of the inner wire assembly, wherein at least a portion of the cutting tip extends distal the distal end of the outer tube;

a coupling chuck secured to the proximal section of the inner wire assembly, wherein the coupling chuck is adapted for connection to a drive mechanism of a motor; and

a housing maintaining the proximal region of the outer tube and the coupling chuck, the housing being adapted for connection to a motor;

wherein a bearing is established between an outer surface of at least a portion of the inner wire assembly and at least a portion of the inner surface of the outer tube distal the housing upon rotation of the inner wire assembly relative to the outer tube;

and further wherein upon final assembly, the wire assumes a shape of the first curved segment.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

45.(Original) The instrument of claim 44, wherein the inner wire assembly is formed of tool steel.

46.(Original) The instrument of claim 45, wherein the tool steel is an M-series tool steel.

47.(Original) The instrument of claim 46, wherein the tool steel is M2 tool steel.

48.(Original) The instrument of claim 44, wherein the outer tube and the inner wire assembly are formed of a metal processed to provide the fatigue strength.

49.(Original) The instrument of claim 48, wherein the metal is subjected to a roll burnishing process.

50.(Original) The instrument of claim 48, wherein the metal is subjected to one of ultrasonic shot peening and laser shot peening.

51.(Original) The instrument of claim 44, wherein the instrument is characterized by the absence of a ball bearing assembly between the outer tube and the inner wire assembly.

52.(Original) The instrument of claim 44, wherein a rotating journal bearing is established between an outer surface of the inner wire assembly and the inner surface of the outer tube upon rotation of the inner wire assembly relative to the outer tube.

53.(Currently Amended) The instrument of claim 44, wherein the ~~inner-wire assembly~~ is a homogenous-wire.

54.(Original) The instrument of claim 53, wherein the journal bearing is established along an entirety of a length of the outer tube distal the housing.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

55.(Cancelled)

56.(Original) The instrument of claim 53, wherein at least a portion of the outer tube distal the housing has a maximum outer diameter of not more than 2 mm.

57.(Original) The instrument of claim 53, wherein the wire has an outer diameter of not more than 0.8 mm.

58.(Original) The instrument of claim 53, wherein an exposed portion of the wire extends distally from the distal end of the outer tube, and further wherein a length of the exposed portion is not greater than 2.54 mm.

59.(Original) The instrument of claim 53, wherein the distal region of the outer tube tapers distally in diameter to the distal end.

60.(Withdrawn) The instrument of claim 44, further comprising:

a sealing tip connected to the distal region of the outer tube, at least a portion of the sealing tip defining an inner diameter that is less than a diameter of the lumen of the outer tube.

61.(Withdrawn) The instrument of claim 60, wherein the sealing tip is a ceramic body.

62.(Withdrawn) The instrument of claim 60, wherein the sealing tip is a tubular body having a proximal portion and a distal portion, the distal portion defining a relaxed state diameter that is less than a diameter of the inner wire assembly, and further wherein upon final assembly, the distal portion of the sealing tip is forced to an expanded state diameter via contact with the inner wire assembly.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

63.(Withdrawn) The instrument of claim 60, wherein the sealing tip is a tubular body shrunk fit to the outer tube and a portion of the inner wire assembly.

64.(Withdrawn) The instrument of claim 44, further comprising:
a cooling sleeve disposed over at least a portion of the outer tube.

65.(Currently Amended) A surgical cutting instrument for use with a motor having a drive mechanism, the instrument comprising:

an outer tube defining a first curved segment, a proximal region terminating at a proximal end, a distal region terminating at a distal end, and a lumen extending from the proximal end to the distal end, the lumen being defined by an inner surface of the outer tube;

an inner wire assembly received within the lumen and comprising a wire, the inner wire assembly including a proximal section and a distal section, wherein the proximal section extends proximally from the proximal end of the outer tube, and further wherein the inner wire assembly is characterized by a Rockwell Hardness of not less than 50 HRC;

a cutting tip connected to the distal section of the inner wire assembly, wherein at least a portion of the cutting tip extends distal the distal end of the outer tube;

a coupling chuck secured to the proximal section of the inner wire assembly, wherein the coupling chuck is adapted for connection to a drive mechanism of a motor; and

a housing maintaining the proximal region of the outer tube and the coupling chuck, the housing being adapted for connection to a motor;

wherein a bearing is established between an outer surface of at least a portion of the inner wire assembly and at least a portion of the inner surface of the outer tube distal the housing upon rotation of the inner wire assembly relative to the outer tube;

and further wherein upon final assembly, the wire assumes a shape of the first curved segment.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

66.(Original) The instrument of claim 65, wherein an exterior surface of the inner wire assembly is coated with a hardened material.

67.(Original) The instrument of claim 66, wherein the hardened material is adapted to provide a dense carbon finish to the inner wire assembly.

68.(Original) The instrument of claim 67, wherein the hardened material is diamond-like carbon.

69.(Original) The instrument of claim 66, wherein the hardened material includes a material selected from the group consisting of zirconium nitride, chrome, fluorocarbon, titanium nitride, and electroless nickel impregnated with PTFE.

70.(Original) The instrument of claim 65, wherein the instrument is characterized by the absence of a ball bearing assembly between the outer tube and the inner wire assembly.

71.(Original) The instrument of claim 65, wherein a journal bearing is established between an outer surface of the inner wire assembly and the inner surface of the outer tube upon rotation of the inner wire assembly relative to the outer tube.

72.(Currently Amended) The instrument of claim 65, wherein the ~~inner-wire assembly~~ is a homogenous-wire.

73.(Original) The instrument of claim 72, wherein the spring wire is a tool steel.

74.(Original) The instrument of claim 72, wherein a rotating journal bearing is established along an entirety of a length of the outer tube distal the housing.

75.(Cancelled)

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

76.(Original) The instrument of claim 72, wherein at least a portion of the outer tube distal the housing has a maximum outer diameter of not more than 2 mm.

77.(Original) The instrument of claim 72, wherein the wire has an outer diameter of not more than 0.8 mm.

78.(Original) The instrument of claim 72, wherein the distal region of the outer tube tapers distally in diameter to the distal end.

79.(Withdrawn) The instrument of claim 65, further comprising:

a sealing tip connected to the distal region of the outer tube, at least a portion of the sealing tip defining an inner diameter that is less than a diameter of the lumen of the outer tube.

80.(Withdrawn) The instrument of claim 79, wherein the sealing tip is a ceramic body.

81.(Withdrawn) The instrument of claim 79, wherein the sealing tip is a tubular body having a proximal portion and a distal portion, the distal portion defining a relaxed state diameter that is less than a diameter of the inner wire assembly, and further wherein upon final assembly, the distal portion of the sealing tip is forced to an expanded state diameter via contact with the inner wire assembly.

82.(Withdrawn) The instrument of claim 79, wherein the sealing tip is a tubular body shrunk fit to the outer tube and a portion of the inner wire assembly.

83.(Withdrawn) The instrument of claim 65, further comprising:

a cooling sleeve disposed over at least a portion of the outer tube.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

84.(Currently Amended) A surgical cutting instrument for use with a motor having a drive mechanism, the instrument comprising:

an outer tube defining a first curved segment, a proximal region terminating at a proximal end, a distal region terminating at a distal end, and a lumen extending from the proximal end to the distal end, the lumen being defined by an inner surface of the outer tube, wherein the inner surface is highly polished, exhibiting a surface roughness of not more than 20 μ inch RMS;

an inner wire assembly received within the lumen and comprising a wire, the inner wire assembly including a proximal section and distal section, wherein the proximal section extends proximally from the proximal end of the outer tube;

a cutting tip connected to the distal section of the inner wire assembly, wherein at least a portion of the cutting tip extends distal the distal end of the outer tube;

a coupling chuck secured to the proximal section of the inner wire assembly, wherein the coupling chuck is adapted for connection to a drive mechanism of a motor; and

a housing maintaining the proximal region of the outer tube and the coupling chuck, the housing being adapted for connection to a motor;

wherein a bearing is established between an outer surface of at least a portion of the inner wire assembly and at least a portion of the inner surface of the outer tube distal the housing upon rotation of the inner wire assembly relative to the outer tube;

and further wherein upon final assembly, the wire assumes a shape of the first curved segment.

85.(Original) The instrument of claim 84, wherein the instrument is characterized by the absence of a ball bearing assembly between the outer tube and the inner wire assembly.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

86.(Original) The instrument of claim 84, wherein a rotational journal bearing is established between an outer surface of the inner wire assembly and the inner surface of the outer tube upon rotation of the inner wire assembly relative to the outer tube.

87.(Original) The instrument of claim 86, further comprising:

a lubricant disposed between the outer surface of the inner wire assembly and the inner surface of the outer tube;

wherein upon rotation of the inner wire assembly relative to the outer tube, the lubricant is adapted to create a hydrodynamic effect.

88.(Currently Amended) The instrument of claim 84, wherein the ~~inner-wire assembly is a homogenous-wire.~~

89.(Original) The instrument of claim 88, wherein the wire is a tool steel.

90.(Original) The instrument of claim 88, wherein the journal bearing is established along an entirety of a length of the outer tube distal the housing.

91.(Cancelled)

92.(Original) The instrument of claim 88, wherein at least a portion of the outer tube distal the housing has a maximum outer diameter of not more than 2 mm.

93.(Original) The instrument of claim 88, wherein the wire has an outer diameter of not more than 0.8 mm.

94.(Original) The instrument of claim 88, wherein the distal region of the outer tube tapers distally in diameter to the distal end.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

95.(Withdrawn) The instrument of claim 84, further comprising:

 a sealing tip connected to the distal region of the outer tube, at least a portion of the sealing tip defining an inner diameter that is less than a diameter of the lumen of the outer tube.

96.(Withdrawn) The instrument of claim 95, wherein the sealing tip is a ceramic body.

97.(Withdrawn) The instrument of claim 95, wherein the sealing tip is a tubular body having a proximal portion and a distal portion, the distal portion defining a relaxed state diameter that is less than a diameter of the inner wire assembly, and further wherein upon final assembly, the distal portion of the sealing tip is forced to an expanded state diameter via contact with the inner wire assembly.

98.(Withdrawn) The instrument of claim 95, wherein the sealing tip is a tubular body shrunk fit to the outer tube and a portion of the inner wire assembly.

99.(Withdrawn) The instrument of claim 84, further comprising:

 a cooling sleeve disposed over at least a portion of the outer tube.

100.(Currently Amended) A surgical instrument for use with a motor having a drive, mechanism, the instrument comprising:

 an outer tube defining a first curved segment, a proximal region terminating at a proximal end, a distal region terminating at a distal end, and a lumen extending from the proximal end to the distal end, the lumen being defined by an inner surface of the outer tube;

 an inner wire assembly received within the lumen and comprising a wire, the inner wire assembly including a proximal section and distal section, wherein the proximal section extends proximally from the proximal end of the outer tube;

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

a cutting tip connected to the distal section of the inner wire assembly, wherein at least a portion of the cutting tip extends distal the distal end of the outer tube;

a coupling chuck secured to the proximal section of the inner wire assembly, wherein the coupling chuck is adapted for connection to a drive mechanism of a motor; and

a housing maintaining the proximal region of the outer tube and the coupling chuck, the housing being adapted for connection to a motor, wherein at least a portion of the outer tube distal the housing has a maximum outer diameter of not more than 2 mm;

wherein a bearing is established between an outer surface of at least a portion of the inner wire assembly and at least a portion of the inner surface of the outer tube distal the housing upon rotation of the inner wire assembly relative to the outer tube;

wherein upon final assembly, the wire assumes a shape of the first curved segment;

and further wherein the instrument is configured to allow rotation of the inner wire assembly relative to the outer tube at a speed of 80,000 RPM without failure of the bearing.

101.(Original) The instrument of claim 100, wherein the instrument is characterized by the absence of a ball bearing assembly between the outer tube and the inner wire assembly.

102.(Original) The instrument of claim 100, wherein a rotating journal bearing is established between an outer surface of the inner wire assembly and the inner surface of the outer tube upon rotation of the inner wire assembly relative to the outer tube.

103.(Original) The instrument of claim 102, further comprising:

a lubricant disposed between the outer surface of the inner wire assembly and the inner surface of the outer tube;

wherein upon rotation of the inner wire assembly relative to the outer tube, the lubricant is adapted to create a hydrodynamic effect.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

104.(Currently Amended) The instrument of claim 100, wherein the ~~inner-wire assembly~~ is a homogenous-wire.

105.(Original) The instrument of claim 104, wherein the wire is a tool steel.

106.(Original) The instrument of claim 104, wherein the journal bearing is established along an entirety of a length of the outer tube distal the housing.

107.(Cancelled)

108.(Original) The instrument of claim 104, wherein the wire has an outer diameter of not more than 0.8 mm.

109.(Original) The instrument of claim 104, wherein an exposed portion of the spring wire extends distally from the distal end of the outer tube, and further wherein the exposed portion has a length of not more than 2.54 mm.

110.(Original) The instrument of claim 104, wherein the distal region of the outer tube tapers distally in diameter to the distal end.

111.(Withdrawn) The instrument of claim 100, further comprising:
a sealing tip connected to the distal region of the outer tube, at least a portion of the sealing tip defining an inner diameter that is less than a diameter of the lumen of the outer tube.

112.(Withdrawn) The instrument of claim 111, wherein the sealing tip is a ceramic body.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

113.(Withdrawn) The instrument of claim 111, wherein the sealing tip is a tubular body having a proximal portion and a distal portion, the distal portion defining a relaxed state diameter that is less than a diameter of the inner wire assembly, and further wherein upon final assembly, the distal portion of the sealing tip is forced to an expanded state diameter via contact with the inner wire assembly.

114.(Withdrawn) The instrument of claim 111, wherein the sealing tip is a tubular body shrunk fit to the outer tube and a portion of the inner wire assembly.

115.(Withdrawn) The instrument of claim 100, further comprising:
a cooling sleeve disposed over at least a portion of the outer tube.

116.(Currently Amended) A surgical cutting instrument for use with a motor having a drive mechanism, the instrument comprising:

- | an outer tube defining a first curved segment, a proximal region terminating at a proximal end, a distal region terminating at a distal end, and a lumen extending from the proximal end to the distal end, the lumen being defined by an inner surface of the outer tube;
- | an inner wire assembly received within the lumen and comprising a wire, the inner wire assembly including a proximal section and distal section, wherein the proximal section extends proximally from the proximal end of the outer tube;
- a cutting tip connected to the distal section of the inner wire assembly, wherein at least a portion of the cutting tip extends distal the distal end of the outer tube;
- a coupling chuck secured to the proximal section of the inner wire assembly, wherein the coupling chuck is adapted for connection to a drive mechanism of a motor; and
- a housing maintaining the proximal region of the outer tube and the coupling chuck, the housing being adapted for connection to a motor;

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

wherein the outer tube exhibits a stiffness of not less than 15 lbf/inch at the distal end relative to a distal point of interface between the outer tube and the housing;

wherein upon final assembly the wire assumes a shape of the first curved segment;

and further wherein a bearing is established between an outer surface of at least a portion of the inner wire assembly and at least a portion of the inner surface of the outer tube distal the housing upon rotation of the inner wire assembly relative to the outer tube.

117.(Original) The instrument of claim 116, wherein the instrument is characterized by the absence of a ball bearing assembly between the outer tube and the inner wire assembly.

118.(Original) The instrument of claim 116, wherein a rotating journal bearing is established between an outer surface of the inner wire assembly and the inner surface of the outer tube upon rotation of the inner wire assembly relative to the outer tube.

119.(Currently Amended) The instrument of claim 116, wherein the ~~inner-wire assembly~~ is a homogenous-wire.

120.(Original) The instrument of claim 119, wherein the wire is a tool steel.

121.(Original) The instrument of claim 119, wherein the journal bearing is established along an entirety of a length of the outer tube distal the housing.

122.(Cancelled)

123.(Original) The instrument of claim 119, wherein at least a portion of the outer tube distal the housing has a maximum outer diameter of not more than 2 mm.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

124.(Original) The instrument of claim 119, wherein the distal region of the outer tube tapers distally in diameter to the distal end.

125.(Withdrawn) The instrument of claim 116, further comprising:

a sealing tip connected to the distal region of the outer tube, at least a portion of the sealing tip defining an inner diameter that is less than a diameter of the lumen of the outer tube.

126.(Withdrawn) The instrument of claim 125, wherein the sealing tip is a ceramic body.

127.(Withdrawn) The instrument of claim 125, wherein the sealing tip is a tubular body having a proximal portion and a distal portion, the distal portion defining a relaxed state diameter that is less than a diameter of the inner wire assembly, and further wherein upon final assembly, the distal portion of the sealing tip is forced to an expanded state diameter via contact with the inner wire assembly.

128.(Withdrawn) The instrument of claim 125, wherein the sealing tip is a tubular body shrunk fit to the outer tube and a portion of the inner wire assembly.

129.(Withdrawn) The instrument of claim 116, further comprising:

a cooling sleeve disposed over at least a portion of the outer tube.

130.(Currently Amended) A surgical cutting instrument for use with a motor having a drive mechanism, the instrument comprising:

an outer tube defining a first curved segment, proximal region terminating at a proximal end, a distal region terminating at a distal end, and a lumen extending from the proximal end to the distal end, the lumen being defined by an inner surface of the

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

outer tube, wherein the inner surface is highly polished, exhibiting a surface roughness of not greater than 20 μ inch RMS;

an inner wire assembly received within the lumen and comprising a wire, the inner wire assembly including a proximal section and distal section, wherein the proximal section extends proximally from the proximal end of the outer tube, wherein the inner wire assembly is formed to exhibit a fatigue strength of at least 75 Kpsi and a hardness of not less than 50 HRC;

a grease lubricant disposed between the inner surface of the outer tube and an outer surface of the inner wire assembly, the grease lubricant exhibiting a dynamic viscosity of not less than 100 mm²/s at 40° C;

a cutting tip connected to the distal section of the inner wire assembly, wherein at least a portion of the cutting tip extends distal the distal end of the outer tube;

a coupling chuck secured to the proximal section of the inner wire assembly, wherein the coupling chuck is adapted for connection to a drive mechanism of a motor; and

a housing maintaining the proximal region of the outer tube and the coupling chuck, the housing being adapted for connection to a motor, wherein at least a portion of the outer tube distal the housing has a maximum outer diameter of not more than 2 mm;

wherein the outer tube exhibits a stiffness of not less than 15 lbf/inch at the distal end relative to a distal point of interface between the outer tube and the housing;

~~and further~~ wherein a hydrodynamic, rotating journal bearing is established between an outer surface of at least a portion of the inner wire assembly and at least a portion of the inner surface of the outer tube distal the housing upon rotation of the inner wire assembly relative to the outer tube;

and further wherein upon final assembly, the wire assumes a shape of the first curved segment;

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

and further wherein the instrument is configured to allow rotation of the inner wire assembly relative to the outer tube at a speed of 80,000 RPM without failure of the journal bearing.

131.(Original) The instrument of claim 130, wherein the instrument is characterized by the absence of a ball bearing assembly between the outer tube and the inner wire assembly.

132.(Currently Amended) The instrument of claim 130, wherein the ~~inner-wire assembly is a homogenous wire.~~

133.(Cancelled)

134.(Original) The instrument of claim 132, wherein the wire is formed of a tool steel material.

135.(Withdrawn) The instrument of claim 130, further comprising:
a sealing tip connected to the distal region of the outer tube, at least a portion of the sealing tip defining an inner diameter that is less than a diameter of the lumen of the outer tube.

136.(Withdrawn) The instrument of claim 135, wherein the sealing tip is a ceramic body.

137.(Withdrawn) The instrument of claim 135, wherein the sealing tip is a tubular body having a proximal portion and a distal portion, the distal portion defining a relaxed state diameter that is less than a diameter of the inner wire assembly, and further wherein upon final assembly, the distal portion of the sealing tip is forced to an expanded state diameter via contact with the inner wire assembly.

Amendment

Applicant: William C. Brunnett et al.

Serial No.: 10/776,835

Filed: February 11, 2004

Docket No.: M190.147.101 / PD266.00

Title: HIGH SPEED SURGICAL CUTTING INSTRUMENT

138.(Withdrawn) The instrument of claim 135, wherein the sealing tip is a tubular body shrunk fit to the outer tube and a portion of the inner wire assembly.

139.(Withdrawn) The instrument of claim 130, further comprising:
a cooling sleeve disposed over at least a portion of the outer tube.

140. – 144.(Cancelled)

145.(Previously Presented) The instrument of claim 1, wherein the lumen of the outer tube has a constant diameter in extension from the housing to the distal end.

146.(New) The instrument of claim 1 wherein the coupling chuck includes a first passageway defining a first diameter to receive the proximal end of the outer tube and a second passageway defining a second diameter, smaller than the first diameter, to receive the inner wire assembly.